ChemMAX® 1






















FEATURES

- High density polyethylene film barrier laminated to spunbond polypropylene Substrate.
- Constructed with stitched and taped seams for superior protection and
- Design features double zips / storm flap front fastening for improved protection and quick and easy donning and removal.
- Lightweight and flexible material for optimum comfort and protection.
- Reinforced knee-pads for comfort & durability.
- Bright yellow color for easy identification.

KEY APPLICATIONS

- Tank cleaning and liquid chemical storage vessel cleaning.
- Pressure spray applications.
- Agricultural spraying and agricultural chemical applications.
- Chemical spill Handling.
- Acid and Alkali handling.



Physical Property	Test Method	Test Result 87g/m ² 100-500	
Basis Weight	ISO 3801:1997		
Abrasion Resistance (No of cycles)	EN530:1994 method 2		
Flex Cracking Resistance	EN ISO7854:1997 method B	1000-2500	
Tensile Strength (MD/CD)	EN ISO 13934-1:1999	120N/73N	
Tear Resistance (MD/CD)	ISO9073-4:1997	81.5N/43.6N	
Puncture Resistance	EN863:1995	13N	
Burst Strength	ISO13938-1:1999,50cm	63.7KPa	
Seam Strength	EN ISO 13935-2:1999	170N	
Electrostatic properties	EN1149-1:2006/EN1149-5:2008 Pass		



428/528,Coverall Coverall with hood, elastic cuffs, walst & ankles. Double front zip fastening. cushioned kneepads.



414,Coverall Coverall with hood and attached boot. elastic cuffs, waist & ankles. Double front zip fastening, cushioned kneepads.



145, coat Coat with hood, zipper closure, elastic cuffs & waist.



301, Pants 025,Apron Pants with Attached ties. elastic waist Size:122x96cm and ankles.



019,Smock Long sleeve, attached ties,



021, Cape hood with rear inlet pigtail, Size: 135x79cm PVC face shield.



101,Lab coat Snap closure, 2 pockets, long sleeve.



024,Sleeve Elastic ends Size: 18" length



903,Boot Cover 905, Boot Cover anti-skid PE sole, elastic top.

Product Style	Color	Seam Method	Sizes	Case Pack
CT15428/CT15414	Yellow O	Heat Sealed Seam	S-XXXL	10
CT1S145/CT1S301	Yellow O	Heat Sealed Seam	S-XXXL	25